

# Universal Co-Op Lubricants

**B660**

**Premium MP GREASE**

## *Product Information Sheet*

### **Description:**

B660 Grease is carefully formulated **lithium complex grease** with oxidation, rust and corrosion inhibitors, extreme pressure (EP) additives for anti-wear and heavy shock loading, and a special polymer to control oil separation during storage. B660 Grease is a high quality multi-purpose type grease available in an NLGI #2 grade and recommended for many applications in agriculture, automotive, construction and industrial environments.

B660 Grease has superior water tolerance and resists water washout from chassis points, exhibits good high temperature capabilities and has outstanding mechanical stability by retaining its consistency in hard use.

### **Features & Benefits:**

The high quality base oils used provide excellent cold temperature performance  
The special polymers reduce the oil separation tendency during storage and inactivity  
The EP additives provide excellent prevention of wear and the capability to withstand heavy shock loading  
The thickener provides excellent resistance to water washout

### **Application:**

Multipurpose #2 EP grease (NLGI Service GC-LB)  
High temperatures  
Shock load conditions  
Moist environments  
Wheel bearings  
Chassis lubrication

### **Health & Safety:**

A complete Material Safety Data Sheet is available upon request. Used grease may be harmful. Avoid prolonged or repeated skin contact. Wash clothing and exposed areas with soap and water.

### **Typical Properties:**

NLGI Grade	NLGI Service	Thickener Type	Texture	Color	Drop Point, °F	Penetration (worked)	Timken OK Load	Oil Properties			
								cSt at 40°C	cSt at 100°C	Flash Point, °F	Pour Point, °F
No. 2	GC-LB	Lith.Comp.	Smooth	Blue-Green	500 (min.)	280	50 lbs. (min.)	185	16.6	365	-15

Typical properties reflect general characteristics, not manufacturing specifications. Variations should be expected.