

MAXTRON[®] MT SAE 50

Full Synthetic Manual Transmission Lubricant

General Description

Maxtron MT is a full synthetic manual transmission lubricant specially formulated for extended drain and severe service in heavy duty transmissions that do not require an EP (extreme pressure) lubricant.

Maxtron MT synthetic base oils provide a high viscosity index and a low pour point. This give excellent high temperature oxidation stability, shear stability, and low temperature flow characteristics. The superior cold flow properties provide easier cold weather shifting, less internal drag, and less gear wear do to quick lubrication at low temperatures. The all-climate, year-round performance leads to less down time, lower maintenance, increased equipment life and the potential for improvement in fuel economy.

Maxtron MT contains effective additives that provide anti-wear, rust, corrosion and oxidation performance to maximize the protection of gears, bearings, synchronizers, shafts and other moving parts.

Expect superior performance in: Eaton, Dana, Fuller, Spicer, Mack, Roadranger, Rockwell, Arvin Meritor heavy duty manual transmissions.

Features and Benefits

Extended OEM Warranty and Drain: Maxtron MT is fully approved by Eaton PS-164 Rev.7 for extended warranty coverage (up to 750,000 miles) and extended drain intervals (up to 500,000 miles) when using this lubricant.

Oil Durability: Designed to protect transmissions against higher torque and horsepower in severe service. Improved high temperature oxidation and thermal stability results in longer oil life by minimizing sludge and varnish deposits.

Oil Pumpability: outstanding low temperature performance results in quicker lubrication to moving parts, less wear, and easier shifting during cold weather operation.

All-Climate Performance: can be used year-round over wide temperature ranges eliminating the need for seasonal changes.

Fuel Economy: has the potential for improved fuel economy over mineral oils with its excellent cold flow properties and resistance to internal friction.

Reduced Cost and Down Time: as a result of longer transmission life, reduced maintenance along with fewer oil changes.

MAXTRON[®] MT SAE 50

Full Synthetic Manual Transmission Lubricant

Typical Application

Maxtron MT full synthetic manual transmission lubricant meets or exceeds the following performance requirements:

- Eaton PS-164 Rev. 7 for extended drain intervals and warranty coverage.
- Mack TO-A Plus
- International TMS 6816
- ZF FreedomLine
- Arvin Meritor (Rockwell) O-81
- API MT-1, GL-1

Typical Customer

Owners and operators of:

- Fleets equipped with the manual transmissions and interested in extended oil drain intervals.
- Fleets interested in ease of shifting, reduced down time, better fuel economy and year-around use.

Total Protection Plan[™] Warranty

Maxtron MT is backed by the Total Protection Plan Warranty program for up to 10 years/10,000 hours on agricultural equipment. See the Warranty program for complete details.

Health & Safety:

A complete material safety data sheet is available upon request. Used motor oil contains combustion by-products, which may be harmful. Avoid prolonged or repeated skin contact. Wash clothing and exposed areas with soap and water. Don't pollute - return used oil to a collection center.

Typical Properties

SAE Grade	50
API Gravity / Lbs. gallon	33.0 / 7.16
Viscosity @ 40°C, cSt (SUS)	132 (678)
Viscosity @ 100°C, cSt (SUS)	17.5 (90)
Viscosity Index	146
Viscosity, cP @ -40 °C	99,800
Pour Point °C / °F	-45 / -49
Flash, COC, °C / °F	221 / 430
Copper Strip Corrosion 3 hrs @ 121 °C / 250 °F	1a

The typical properties listed reflect the general characteristics of the product, and are not manufacturing specifications. Normal batch-to-batch variations should be expected.